



Product Specification Sheet

Reflect-A-Cloth, Reflect-A-Sleeve™, CIS™ Cool Intake System, & Reflect-A-Boot™
Part #'s: 270034, 270114, 270034R, 270078R, 270100R, 274034, 274114,
274400, 410200, 710000, & 710040

Product Overview

Extreme flexibility makes it excellent for firewalls, floorboards, hood, etc. The special "Gentex" coating has excellent adhesion and durability properties. Face aluminized side of cloth towards heat source. Material is over 90% reflective of radiant heat.

Physical Characteristics

Fiber Content	Fiberglass	Weave	Satin
Coating/Finish	Aluminum	Flexibility	Excellent
Color	Chrome	Electrical	Conductive
Weight	11oz/sqyd	Chemical	Non-reactive
Thickness	.012"	Widths	54"

Performance Characteristics

Break Strength (warp)	350lbs	Afterflame	1 second
Break Strength (fill)	300lbs	Char Length	.5"
Tear Strength (warp)	15lbs	Afterglow	5 seconds
Tear Strength (fill)	15lbs		

Temperature Parameters

Reflectivity @ 3000°F	15 seconds
Base Fabric Service	1100 °F
Melt	>1200 °F

Proudly made in the USA

(800) 750-3978 (760) 751-0441 USA
www.heatshieldproducts.com