



#RACETESTED



Heat Shield Barrier

THERMAFLECT™ TAPE

Thermaflect™ Tape reflects up to 90% of radiant heat away from wires, lines, cables and hoses, protecting them from ambient heat, and it withstands 1100°F continuous radiant heat (requires minimum of 1 inch airspace) and 500°F of direct contact. Thermaflect Tape™ insulates components without requiring disassembly for installation, or it can be used to hold other thermal-barrier products in place. Thermaflect Tape™ can also be used as a quick solution to radiant heat-damage problems — use it at a track to control a hot spot. Durable cloth construction makes it last longer than similar products. Thermaflect™ Tape is easy to cut and install, thanks to our high-temperature self-adhesive backing that sticks to any clean surface. Thermaflect Tape™ rolls are available up to 150 feet long, with minimum roll sizes applying. Thermaflect™ Tape is a must-have for your shop or racetrack toolbox.



FEATURES:

-  **1100°F**  **2000°F**
CONTINUOUS INTERMITTENT
- Capable of reflecting over 90% of radiant heat
- Flexible; bends and conforms to almost any shape
- Simple installation in minutes
- Made in the USA

PART NO.	DESCRIPTION
340001	1-1/2 in x 3 ft
340020	1-1/2 in x 20 ft heat shield tape
340250	2 in x 50 ft
340410	4 in x 10 ft heat shield tape
721150	0.032 th x 12 in x 50 ft Roll

(760) 751-0441

HEATSHIELDPRODUCTS.COM