

CATCH CAN SHIELD™

Product Installation



Tools Required

- Safety glasses, gloves, and dust mask
- Heavy-duty scissors or razor knife
- Non residue cleaner
- Paper (optional)

Installation Tips

Catch can surface temperature should be at least 65°F when applying, sticking onto anything colder may not allow adhesive to set up properly.

We strongly recommend rubbing the surface with a pre-paint cleaner or isopropyl alcohol (or other non-residue cleaner) after cleaning and degreasing.



Installation Steps

1. Put on PPP - gloves, dust mask, and safety glasses
2. Create a template with paper then transfer your template onto the Catch Can Shield.
3. Degrease and clean surface of any residual chemicals, using carburetor spray or other cleaner/degreaser.
4. Carefully peel the adhesive backing off the Catch Can Shield. It may be necessary to use razor blade or utility knife to start peeling from one corner.
5. Lay one edge of the Catch Can Shield and work out slowly to ensure no "bubbles" occur. Air bubbles will cause the material to not stick and fall off.
6. Press the Catch Can Shield firmly onto the catch can, hold while pressing down for a minute.
7. Use included edging tape to seal ends and seams of the Catch Can Shield. Clean the edge of Catch Can Shield and the surface of the catch can with the pre-paint cleaner or isopropyl alcohol and the surface it will be used on.
8. Install catch can, go racing.

